

Stainless Steel (inc. High Performance) - 1.4542 / 17.4

Round Bar

Properties

Stock		Chemical Properties																																																																																							
Dia (in)	Weight/m (Kg)	Element				Chemical Composition %																																																																																			
1/2	0.98	Carbon (C)				0.00 - 0.07																																																																																			
5/8	1.54	Silicon (Si)				0.00 - 1.00																																																																																			
3/4	2.21	Manganese (Mn)				0.00 - 1.00																																																																																			
7/8	3.01	Nickel (Ni)				3.00 - 5.00																																																																																			
1	3.93	Chromium (Cr)				15.00 - 17.50																																																																																			
1 1/4	6.21	Copper (Cu)				3.00 - 5.00																																																																																			
1 1/2	8.94	Sulphur (S)				0.00 - 0.030																																																																																			
1 3/4	12.18	Phosphorous (P)				0.00 - 0.040																																																																																			
2	15.90	Columbium (Cb)				0.15 - 0.45																																																																																			
2 1/4	20.13	Heat Treatment & Mechanical Properties <table border="1"> <thead> <tr> <th>Condition</th> <th>Heat Treatment °C</th> <th>0.2% Proof Stress (Mpa min)</th> <th>UTS (Mpa min)</th> <th>Elongation (%)</th> <th>Reduction of Area % min</th> <th>Hardness Brinell (HB)</th> <th>Impact Toughness J min (Room temp)</th> </tr> </thead> <tbody> <tr><td>A</td><td>1040 cool to below 32</td><td>-</td><td>-</td><td>-</td><td>-</td><td>363 max</td><td>-</td></tr> <tr><td>H900</td><td>+480 1hr</td><td>1170</td><td>1310</td><td>10</td><td>40</td><td>388 min</td><td>-</td></tr> <tr><td>H925</td><td>+495 4hrs</td><td>1070</td><td>1170</td><td>10</td><td>44</td><td>373 min</td><td>6.8</td></tr> <tr><td>H1025</td><td>+550 4hrs</td><td>1000</td><td>1070</td><td>12</td><td>45</td><td>331 min</td><td>20</td></tr> <tr><td>H1075</td><td>+580 4hrs</td><td>860</td><td>1000</td><td>13</td><td>45</td><td>311 min</td><td>27</td></tr> <tr><td>H1100</td><td>+595 4hrs</td><td>795</td><td>965</td><td>14</td><td>45</td><td>302 min</td><td>34</td></tr> <tr><td>H1150</td><td>+620 4hrs</td><td>725</td><td>930</td><td>16</td><td>50</td><td>277 min</td><td>41</td></tr> <tr><td>H1150M</td><td>+760 2hrs / +620 4hrs</td><td>520</td><td>795</td><td>18</td><td>55</td><td>255 min</td><td>75</td></tr> <tr><td>H1150D</td><td>+620 4hrs</td><td>725</td><td>860</td><td>16</td><td>50</td><td>255 min - 311 max</td><td>41</td></tr> </tbody> </table>								Condition	Heat Treatment °C	0.2% Proof Stress (Mpa min)	UTS (Mpa min)	Elongation (%)	Reduction of Area % min	Hardness Brinell (HB)	Impact Toughness J min (Room temp)	A	1040 cool to below 32	-	-	-	-	363 max	-	H900	+480 1hr	1170	1310	10	40	388 min	-	H925	+495 4hrs	1070	1170	10	44	373 min	6.8	H1025	+550 4hrs	1000	1070	12	45	331 min	20	H1075	+580 4hrs	860	1000	13	45	311 min	27	H1100	+595 4hrs	795	965	14	45	302 min	34	H1150	+620 4hrs	725	930	16	50	277 min	41	H1150M	+760 2hrs / +620 4hrs	520	795	18	55	255 min	75	H1150D	+620 4hrs	725	860	16	50	255 min - 311 max	41
Condition	Heat Treatment °C									0.2% Proof Stress (Mpa min)	UTS (Mpa min)	Elongation (%)	Reduction of Area % min	Hardness Brinell (HB)	Impact Toughness J min (Room temp)																																																																										
A	1040 cool to below 32									-	-	-	-	363 max	-																																																																										
H900	+480 1hr									1170	1310	10	40	388 min	-																																																																										
H925	+495 4hrs									1070	1170	10	44	373 min	6.8																																																																										
H1025	+550 4hrs									1000	1070	12	45	331 min	20																																																																										
H1075	+580 4hrs									860	1000	13	45	311 min	27																																																																										
H1100	+595 4hrs									795	965	14	45	302 min	34																																																																										
H1150	+620 4hrs									725	930	16	50	277 min	41																																																																										
H1150M	+760 2hrs / +620 4hrs									520	795	18	55	255 min	75																																																																										
H1150D	+620 4hrs									725	860	16	50	255 min - 311 max	41																																																																										
2 1/2	24.85																																																																																								
2 3/4	29.71																																																																																								
3	35.34																																																																																								
3 1/4	42.00																																																																																								
3 1/2	48.69																																																																																								
3 3/4	55.91																																																																																								
4	63.62																																																																																								
4 1/4	71.80																																																																																								
4 1/2	79.52																																																																																								
4 3/4	87.65																																																																																								
5	98.17																																																																																								
5 1/4	108.24																																																																																								
5 1/2	118.79																																																																																								
5 3/4	129.84																																																																																								
6	141.37																																																																																								
6 1/4	153.42																																																																																								
6 1/2	165.92																																																																																								
6 3/4	178.92																																																																																								
7	192.42																																																																																								
7 1/2	220.89																																																																																								
8	251.33																																																																																								
8 1/2	283.72																																																																																								
9	318.09																																																																																								
9 1/2	354.41																																																																																								
10	395.80																																																																																								
10 1/2	432.95																																																																																								
11	477.21																																																																																								
12	566.23																																																																																								
13	666.88																																																																																								
14	771.42																																																																																								
15	889.22																																																																																								
16	1008.25																																																																																								

Modulus of elasticity, GPa at

20 °C (68°F)	100 °C (210 °F)	200 °C (390 °F)	300 °C (570 °F)	400 °C (750 °F)
10.9 (6.1)	11.0 (6.1)	11.0 (6.1)	11.1 (6.2)	11.2 (6.2)

Physical Properties

Property	Value	Unit
Density at 20°C (68 °F)	7.80	kg/dm ³
Thermal Conductivity at 20°C (68 °F)	16.0	W/m.K
Specific Heat at 20°C (68°F)	500	J/kg.K
Elastic Resistivity at 20°C (68°F)	0.71	Ohm.mm ^{2/m}
Modulus of elasticity at 20°C (68°F)	200 x 10 ³	200 x 10 ³
Magnetic Properties		magnetic

Thermal Expansion Coefficient between 20degc (68 degf) and

temperature below 10⁻⁶/degc (10⁻⁶/degf)

100 °C (210 °F)	200 °C (390 °F)	300 °C (570 °F)	400 °C (750 °F)
10.9	-	11.1	-

Disclaimer

This data is indicative only and as such is not to be relied upon in place of the full specification. In particular, mechanical property requirements vary widely with temper, product and product dimensions. All information is based on our present knowledge and is given in good faith. No liability will be accepted by the Company in respect of any action taken by any third party in reliance thereon.

The information provided in this datasheet has been drawn from various recognised sources, including EN Standards, recognised industry references (printed & online) and manufacturers' data. No guarantee is given that the information is from the latest issue of those sources or about the accuracy of those sources.

Material supplied by the Company may vary significantly from this data, but will conform to all relevant and applicable standards.

As the products detailed may be used for a wide variety of purposes and as the Company has no control over their use; the Company specifically excludes all conditions or warranties expressed or implied by statute or otherwise as to dimensions, properties and/or fitness for any particular purpose, whether expressed or implied.

Advice given by the Company to any third party is given for that party's assistance only and without liability on the part of the Company. All transactions are subject to the Company's current Conditions of Sale. The extent of the Company's liabilities to any customer is clearly set out in those Conditions; a copy of which is available on request.